


## **COMMERCIAL SHOWER SYSTEMS**

## 2.5 GPM SHOWER SYSTEM KIT


WITH HAND SHOWER



### **GENERAL DESCRIPTION:**

Complete commercial shower system includes: an R121SS pressure balance valve and trim, a wall supply with 1/2" NPT female inlet and 1/2" NPSM male outlet, a 59" (1500 mm) metal shower hose, vacuum breaker, a 3-function hand shower with pause feature, and a 36" slide bar.

Valve features a cast brass body, washerless 47 mm ceramic disc valve cartridge with volume and temperature control, back-to-back capability, integrated check valves and hot limit safety stop. Pressure balancing cartridge maintains constant output temperature in response to changes in relative hot and cold supply pressure. Universal inlets/outlets. With screwdriver stops. Rough-in plaster guard designed for use as thin wall mounting adapter. Durable metal handle. 3-function water saving hand shower with pause feature and 1.5 gpm/5.7 /Lmin. flow restrictor. Slide Bar features an adjustable hand shower holder which can be set at any height or position along the bar and angle up to 45°.



#### **MODEL NUMBER:**

# ☐ 1662.221 Commercial Shower System Kit

Includes:

Universal pressure balance Shower R121SS
 Valve with screwdriver stops

• Colony Soft Valve Only Trim T675.500.002 • 3-Function Hand Shower 1660.767.002

with Pause Feature

In-Line Vacuum Breaker
 Metal Hose
 Wall Supply
 36" Slide Bar
 1660.400.002
 8888.035.002
 8888.037.002
 1660.236.002

### ☐ 1662.221XV Commercial Shower System Kit

- SAME AS ABOVE
- LESS Shower Valve

#### PRODUCT FEATURES:

#### VALVE:

Universal Inlets / Outlets: 1/2" NOM Copper Sweat or 1/2" NPT

Cast Brass Valve Body: Durable. Ideal material for prolonged contact with water.

**Ceramic Disc Valve Cartridge:** Assures a lifetime of drip-free performance. Allows easy control over both water temperature and volume.

Pressure Balancing Valve Cartridge: Maintains constant output temperature in response to changes in relative hot and cold supply pressure. Diaphragm system with integrated check valves engineered to eliminate cross flow. Avoids failure due to mineral deposits - ideal for use in hard water.

**Back-to-Back Capability:** Hot and cold can be reversed quickly and easily.

**Adjustable Hot Limit Safety Stop:** Limits the amount of hot water allowed to mix with cold. Reduces the risk of accidental scalding.

**Exclusive Plaster Guard:** Plaster guard is designed to protect valve during installation and serve as a mounting plate for thin-wall installations. Two-piece design allows valve to be tested prior to trim installation.

Wide Rough-in Range: From 1-5/8" to 3-1/4".

#### **HAND SHOWER WITH PAUSE FEATURE:**

**ADA-Compliant:** Non-positive shut-off button on handle reduces flow to a trickle.

#### 36" SLIDE BAR:

**Simple Height Adjustment:** Allows positioning of the hand shower anywhere along the bar.

NOT DESIGNED TO BE A GRAB BAR.

### SUGGESTED SPECIFICATION

Shower system shall feature a wall supply with 1/2" NPT female inlets and 1/2" NPSM male outlet, 59" metal hose, vacuum breaker, 2.5 gpm/9.5 L/min. 3-function hand shower with pause feature and a 36" slide bar. Pressure Balance valve shall feature a cast brass body. Shall feature ceramic disc valve cartridge which controls water temperature and volume. Shall also feature hot limit safety stop. Fitting shall be American Standard Model # 1662.221.002.

© 2018 AS America Inc. Revised 7/18



# **COMMERCIAL SHOWER SYSTEMS**

2.5 GPM SHOWER SYSTEM KIT


WITH HAND SHOWER

## **CODES AND STANDARDS**

These products meet or exceed the following codes and standards:

ASME A112.18.1 ASSE 1016 CSA B 125 ANSI A117.1

		Finish
Product		Polished Chrome
Number	Description	002
1662.221	Commercial Shower System Kit. Contains pressure balance valve with volume and temperature control, trim kit, 3-function hand shower with pause feature, metal hose, vacuum breaker, wall supply and 36" slide bar. 2.5 gpm/9.5 L/min.	



PART OF LIXIL

© 2018 AS America Inc.

Revised 7/18